



SHELL ADVANCE RACING ENGINE OIL 4T 20W-60

Application

Shell Advance Racing Engine Oil 4T 20W-60 is a high performance 4-stroke lubricant designed for use in Superbike engines.

Characteristics

Designed for the demands of Superbike engines. Specially suitable for endurance racing.

- Maximum engine protection with high power
- Excellent shear stability
- Low oil consumption
- Suitable for wet clutches

Health, safety and environment

Shell Advance Racing Engine Oil 4T 20W-60 is unlikely to present any significant health or safety hazard when properly used in the recommended application, and good standards of industrial and personal hygiene are maintained.

Avoid contact with skin. Use impervious gloves with used oil. After skin contact, wash immediately with soap and water.

For further guidance on Product Health and Safety refer to the appropriate Shell Product Safety Data Sheet.

Protect the environment. Take used oil to an authorised collection point. Do not discharge into drains, soil or water.

Physical characteristics

| | | |
|---------------------|------------|------------------------|
| Viscosity Grade | SAE 20W-60 | |
| Kinematic Viscosity | @ 40° C | 173 mm ² /s |
| | @ 100°C | 24 mm ² /s |
| Viscosity Index | 172 | |
| Dynamic Viscosity | @ -15°C | 4,490 mPas |
| Density | @ 15°C | 0.893 kg/l |
| Flash Point | PMCC | 280°C |
| Pour Point | - 20°C | |



These characteristics are typical of current production. Whilst future production will conform to Shell's specification, variations in these characteristics may occur. July 2004